

Electric Multi-Turn Actuator MO 4



Type number:	154	
Switching-off torque:	130 to 250	[Nm]
Operating speed:	10 to 50	[min ⁻¹]
Number of revolutions:	1,75 to 685	
Ambient temperature:	-25 to +55	[°C]
Protection enclosure:	IP 55, IP 67	
Operating position:	the motor axis should be in horizontal position +/-15°	
Weight:	38 to 50	[kg]

Standard Specification

- Supply voltage 3x400 V AC
- Terminal board connection
- 2 torque switches
- 2 position switches
- 2 additional position switches
- Space heater with thermal switch
- Mechanical connection ISO 5210 - flange F14
- Mechanical position indicator
- Torque switches blocking in limit position
- Manual control
- Protection enclosure IP 55

Options

- Supply voltage 3x380 V AC, 230/220 V AC - after consulting with producer
- Protection of the motor against overheating
- Connector connection
- Tandem switches
- Transmitter:- potentiometer: 1x100 Ω, 1x2000 Ω, 2x100 Ω, 2x2000 Ω- electronic position transmitter 0/4 - 20 mA, (passive/active)- CPT (capacitive) 4 - 20 mA, (passive/active)
- Local control
- Mechanical connection:- ISO 5210, shape A- other non-standard connection
- Protection enclosure IP 67