

Electric Multi-Turn Actuator MO 5



Type number:	155	
Switching-off torque:	250 to 1000	[Nm]
Operating speed:	15 to 100	[min ⁻¹]
Number of revolutions:	1,25 to 500	
Ambient temperature:	-25 to +55	[°C]
Protection enclosure:	IP 55, IP 67	
Operating position:	the motor axis should be in horizontal	
Weight:	93,5 to 103	[kg]

Standard Specification

- Supply voltage 3x400 V AC
- Terminal board connection
- 2 torque switches
- 2 position switches
- 2 additional position switches
- Space heater with thermal switch
- Mechanical connection - flange
- Mechanical position indicator
- Torque switches blocking in limit position
- Manual control
- Protection enclosure IP 55

Options

- Supply voltage 230 V AC, 220 V AC, 3x380 V AC, other - after consulting with producer
- Protection of the motor against overheating
- Connector connection
- Tandem switches
- Transmitter:- potentiometer: 1x100 Ω, 1x2000 Ω, 2x100 Ω, 2x2000 Ω- electronic position transmitter 0/4 - 20 mA, (passive/active)- CPT (capacitive) 4 - 20 mA, (passive/active)
- Local control
- Mechanical connection:- ISO 5210, shape A- other non-standard connection
- Protection enclosure IP 67