

## Electric Multi-Turn Actuator MOR 3.4PA



Type number:	<b>106</b>	
Switching-off torque:	<b>100 to 350</b>	[Nm]
Operating speed:	<b>10 to 80</b>	[min <sup>-1</sup> ]
Number of revolutions:	<b>1 to 500</b>	
Ambient temperature:	<b>-25 to +55</b>	[°C]
Protection enclosure:	<b>IP 55, IP 67</b>	
Operating position:	<b>the motor axis should be in horizontal position +/-15°</b>	
Weight:	<b>42 to 45</b>	[kg]

### Standard Specification

- Supply voltage 3x400 V AC
- Terminal board connection
- Protection of the motor against overheating
- Switching off in limit positions from the position or torque
- Adjustable switching off-torque from 50% to 100%
- Torque blocking in limit positions
- Torque blocking during the start
- 7 freely programmable relays R1, R2, RE1...RE5
- 2 relays READY
- Control by unified signal 0/4 - 20 mA, 4 - 12 mA, 12 - 20 mA, or 0/2 - 10 V (not for DMS3 in 2P version)
- Control voltage for remote control 24 V DC
- Impulse control (inching duty)
- Timing mode / regime of operation
- Safety function ESD (failure reaction)
- Electronic position transmitter 4-20 mA passive (not for DMS3 in 2P version)
- Auxiliary voltage output 24 V DC, max. 100 mA for supply of the control inputs
- Output for failure messages
- Space heater operated by control unit
- LED position indicator
- Communication interface RS 232
- Programme for parameters setting by PC
- Mechanical connection - flange ISO 5210, DIN 3338
- Manual control

### Options

- Local control