

Electric Multi-Turn Actuator SOR 2



Type number:	062	
Switching-off torque:	5 to 100	[Nm]
Operating speed:	10 to 40	[min ⁻¹]
Number of revolutions:	0,5 to 330	
Ambient temperature:	-25 to +55	[°C]
Protection enclosure:	IP 65, IP 67	
Operating position:	any position	
Weight:	12 to 18,5	[kg]

Standard Specification

- Supply voltage 230 V AC, 3x400 V AC
- Terminal board connection
- 2 torque switches
- 2 position switches
- 2 additional position switches
- Positioner 0/4 - 20 mA, 0 - 10 V
- Mechanical connection ISO 5210, flange F10
- Space heater with thermal switch
- Mechanical position indicator
- Manual control
- Protection enclosure IP 65

Options

- Supply voltage 220 V AC, 3x380 V AC, 24 V AC, 24 V DC
- Connector connection
- Tandem switches
- Transmitter:- potentiometer: 1x100 Ω, 1x2000 Ω, 2x100 Ω, 2x2000 Ω- electronic position transmitter 0/4 - 20 mA, (passive/active)- CPT (capacitive) 4 - 20 mA, (passive/active)
- Local control
- Mechanical connection:- ISO 5210, shape A- DIN 3338, shape C- other non-standard connection
- Protection enclosure IP 67