

## Electric Part-Turn Actuator SP 2.3



Type number:	<b>283</b>	
Switching-off torque:	<b>290</b>	[Nm]
Operating time:	<b>20 to 160</b>	[s/90°]
Operating angle:	<b>60° to 360°</b>	
Ambient temperature:	<b>-25 (-50) to +55</b>	[°C]
Protection enclosure:	<b>IP 67</b>	
Operating position:	<b>any position</b>	
Weight:	<b>15 to 16</b>	[kg]

### Standard Specification

- Supply voltage 230 V AC
- Terminal board connection
- 2 torque switches
- 2 position switches
- Mechanical connection ISO 5211 - flange F07/F10
- Mechanical position indicator
- Mechanical stop ends
- Manual control

### Options

- Supply voltage 220 V AC, 3x400 V AC, 3x380 V AC, 24 V AC, 24 V DC
- Connector connection
- 2 additional position switches
- Reverse contactors
- Transmitter:- potentiometer: 1x100 Ω, 1x2000 Ω, 2x100 Ω, 2x2000 Ω  
electronic position transmitter 0/4 - 20 mA, (passive/active)- CPT (capacitive) 4 - 20 mA, (passive/active)
- Space heater with / without thermal switch
- Local control
- Version with stand, lever and pull-rod