

SG50

EPDM Gaskets
Stub Gaskets



Size	E	S	Kg.
1/2"	34	3	0.020
3/4"	41	3	0.021
1"	50	3	0.026
1 1/4"	61	3	0.029
1 1/2"	73	3	0.034
2"	90	3	0.035
2 1/2"	106	3	0.038
3"	125	3	0.040
4"	150	4	0.043
5"	188	4	0.059
6"	213	4	0.073
8"	274	4	0.088

SF10

EPDM Gaskets
FF BS10 Table E



Size	E	S	Holes	Kg.
1/2"	95	3	4	0.030
3/4"	101	3	4	0.036
1"	114	3	4	0.038
1 1/4"	120	3	4	0.040
1 1/2"	135	3	4	0.055
2"	156	3	4	0.057
3"	186	3	4	0.099
4"	219	3	8	0.114
6"	279	3	8	0.160

SF16

EPDM Gaskets
FF BS4504 PN16



Size	E	S	Holes	Kg.
1/2"	95	3	4	0.030
3/4"	101	3	4	0.036
1"	114	3	4	0.038
1 1/4"	120	3	4	0.040
1 1/2"	135	3	4	0.055
2"	156	3	4	0.057
2 1/2"	176	3	4	0.078
3"	186	3	8	0.099
4"	219	3	8	0.114
6"	279	3	8	0.160

Dimensions in mm

This data sheet is designed as a guide and should not be regarded as wholly accurate in every detail. We reserve the right to amend the specification of any product without notice.

GB10

Galvanised Mild Steel Backing Rings
BS10 Table E



GB16

Galvanised Mild Steel Backing Rings
BS4504 PN16



GB15

Galvanised Mild Steel Backing Rings
BS1560 ASA150



Size	E	S	P.C.D.	Holes	Kg.
1/2"	95	6	67	4	0.210
3/4"	102	6	73	4	0.230
1"	115	6	83	4	0.290
1 1/4"	120	6	87	4	0.290
1 1/2"	134	8	98	4	0.370
2"	152	8	115	4	0.590
2 1/2"	165	8	127	4	0.890
3"	185	8	145	4	1.060
4"	216	8	178	8	1.190
5"	254	10	210	8	2.070
6"	290	10	235	8	2.160
8"	337	10	292	8	2.800

Size	E	S	P.C.D.	Holes	Kg.
1/2"	95	6	65	4	0.350
3/4"	105	6	75	4	0.410
1"	115	6	85	4	0.490
1 1/4"	140	6	100	4	0.730
1 1/2"	150	6	110	4	0.820
2"	165	8	125	4	1.220
2 1/2"	185	8	145	4	1.480
3"	200	8	160	8	1.500
4"	220	8	180	8	1.680
5"	250	10	210	8	1.940
6"	285	10	240	8	2.700
8"	340	10	295	12	3.230

Size	E	S	P.C.D.	Holes	Kg.
1/2"	89	6	60	4	0.190
3/4"	99	6	70	4	0.230
1"	108	6	80	4	0.290
1 1/4"	118	6	90	4	0.300
1 1/2"	127	6	98	4	0.360
2"	152	8	121	4	0.790
3"	190	8	152	4	1.240
4"	229	8	190	8	1.560
5"	254	10	216	8	2.070
6"	280	10	241	8	2.730
8"	343	10	298	8	3.340

Dimensions in mm

This data sheet is designed as a guide and should not be regarded as wholly accurate in every detail. We reserve the right to amend the specification of any product without notice.