

## 2/2 Way Piston Actuated Valve G 1/2" to 3/4", Compact Version – Stainless Steel

Specifications	
Type: PG NC flow over seat 1 → 2	
Type RPG: NO flow under seat 2 → 1	
Type: BPG NC bi-directional flow over/under seat 1 → 2 / 2 → 1	
Type: DPG DA flow over/under seat 1 ↔ 2	
Media	Water, oil, air, aggressive media, steam <sup>1</sup>
Media Temperature	-10 to +180 °C
Ambient Temperature	-10 to +60 °C
Pilot Media <sup>2</sup>	Instrument air, inert gases
Body Material	Cast AISI 316L (CF3M), see page 7
Bonnet Material	Cast AISI 316L (CF3M), see page 7
Actuator Body Material	Polyamide + 30% glass fiber
Seal Material	PTFE
Position Indicator	As standard

### Features and Benefits

- Waterhammer-free design for BPG - DPG (with flow direction 2→1)
- Actuator housing rotation 360°
- Design suitable for vacuum applications up to 10<sup>-2</sup> mbar
- ATEX version available



CE Ex ATEX

Ex II 2 G Ex h IIC T6 T4 T5 Gb

Ex II 2 D Ex h IIIC T85°C T100°C T135°C Db


### Options Available

NPT connection (e.g. code PN205CTW00)  
ATEX version (e.g. code PG205TTW00)

### Accessories

Position module, travel switch kit, pilot solenoid valves see pages 34/35/36

Dimensions & Weights		DN15	DN20
Actuator	[mm]	Ø 45	
A	[mm]	65	75
B	[mm]	144	149
C	[mm]	136	142
D	[mm]	123	126
E	[mm]	57	57
Weight	[kg]	0.8	0.9



The products listed below comply with the requirements of the European Pressure Equipment Directive 2014/68/UE and carry the CE mark when required. The products fall within the following Pressure Equipment Directive categories:

Bodies	Group 1 gases	Group 1 liquids and Group 2 other fluids
DN15 to DN20 (PN40)	art. 4.3	art. 4.3

### WARNING!

According to the European Pressure Equipment Directive 2014/68/UE, liquids whose saturated vapour pressure at the maximum allowable temperature is more than 0,5 barg shall be considered as gases.

Valve	Body Connection	DN	Flow Rate Kvs	Working Pressure <sup>1</sup> Min.	Working Pressure <sup>1</sup> Max.	Flow Direction	Pilot Pressure <sup>3</sup> Min.	Pilot Pressure <sup>3</sup> Max.	Actuator Ø	Function
Code	[ISO 228G]	[mm]	[l/min]	[barg]	[barg]	—	[barg]	[barg]	[mm]	—
PG205CTW00	1/2"	15	75	0	16	1 → 2	3.8	10	45	NC
PG206CTX00	3/4"	20	133	0	16	1 → 2	5.8	10		
RPG205CTW00	1/2"	15	75	0	16	2 → 1	4	10	45	NO
RPG206CTX00	3/4"	20	133	0	16	2 → 1	6.2	10		
BPG205CTW00	1/2"	15	75	0	16 / 16	1 → 2 / 2 → 1	6.2 / 5	10	45	NC bidirectional
BPG206CTX00	3/4"	20	133	0	16 / 7	1 → 2 / 2 → 1	8.7 / 5	10		
DPG205CTW00	1/2"	15	75	0	16 / 16	1 ↔ 2	3	10	45	DA
DPG206CTX00	3/4"	20	133	0	16 / 16	1 ↔ 2	5	10		

### Notes

1. Steam max. working pressure 10 bar (9 barg)
2. Please contact M&M sales Department for other pilot media
3. Minimum pilot pressure at the max. working pressure: for lower working pressures please refer to the comparative charts
4. Pav ATEX performances are the same as weather proof pav